

100% Duty Compressors can run 24 hours x 7 days a week at up to 6.9 bar at 22 Centigrade
ViAir compressors run at lower Amps for the same air volume than the clones, which means
better design, lower operating temperatures and thus longer compressor & battery life

12V DC, Oil-Less Design, Moisture & Dust Resistant, , Inline non-return valve
Automatic reset Thermal overload protector, Hi Performance PTFE piston Rings
Stainless Steel valves, Remote mountable intake filter (with Spares)
mounting includes rubber vibration isolators, Stainless steel braided leader hose
Large Cooling Fins on Cylinder, Gearless Direct Drive Motor, Anodised Aluminum alloy cylinder

GRV33050



Chrome Body
Max Current **17** Amps,
Max Working Pressure
10.3 Bars,
Weight 3.6 Kg.

Pumps **42** Litres per minute at 0 bar,
33.5 at 1 bar, 31.5 at 2 bar, 22.5 at 7
bar, 17 at **10** bar.
Fills 11.4L Tank 0-7bar=**204**secs,
31x10.5" tyre 0-2bar=280 secs,
1-2bar=230 secs

GRV38003



Max Current **16** Amps,
Max Working Pressure
13.7 Bars,
Weight 3.6 Kg.

Pumps **42** Litres per minute at 0 bar,
32.5 at 1 bar, 31.0 at 2 bar, 23 at 7
bar,
11.5 at **14** bar
Fills 11.4L Tank 0-7bar=**204**secs,
31x10.5" tyre 0-2bar=320 secs,
1-2bar=170 secs

GRV45040



=GRV45012 Max Current
17 Amps,
Max Working Pressure
10.3 Bars,
Weight 4.4 Kg.
(Twinpack = free relay
and press switch)

Pumps **47** Litres per minute at 0 bar,
42 at 1 bar, 38.5 at 2 bar, 26.5 at 7
bar, 21 at **10** bar.
Fills 11.4L Tank 0-7bar=**151**secs,
31x10.5" tyre 0-2bar=295 secs,
1-2bar=160 secs

GRV48043



Chrome body, **3/8** port
Max Current **20** Amps,
Max Working Pressure
13.7 Bars,
Weight 5 Kg.
(Twinpack = free relay
and press switch)

Pumps **50** Litres per minute at 0 bar,
46 at 1 bar, 43 at 2 bar, 31.5 at 7 bar,
15.5 at **14** bar.
Fills 11.4L Tank 0-**10**bar=**246**secs,
31x10.5" tyre 0-2bar=245secs,
1-2bar=130secs

GRV55050



3/8 port, Fan, Built in **safety**
valve,
Max Current **30** Amps,
Max Working Pressure **10.3**
Bars, Restart 13.8 bars
Weight 8.4 Kg.

Pumps **82** Litres per minute at 0 bar,
70 at 1 bar, 66 at 2 bar, 39.5 at 7 bar,
24 at **10** bar.
Fills 11.4L Tank 0-7bar=**95**secs,
31x10.5" tyre 0-2bar=**135** secs,
1-2bar=75 secs

GRV45058



24V DC only, Industrial
Grade
Max Current **11** Amps,
Max Working Pressure **10.3**
Bars,
Weight 5.125 Kg. Dim L250,
H165, W100, Temp -4 to +70
Celcius

Pumps **50** Litres per minute at 0 bar,
44.5 at 1 bar, 41 at 2 bar, 27 at 7 bar,
21.5 at **10** bar.
Fills 11.4L Tank 11.4L 0-
7bar=**139**secs,
31x10.5" tyre 0-2bar=245 secs,
1-2bar=130 secs