

12V DC, Oil-Less Design, Moisture & Dust Resistant, Anodised Aluminium alloy cylinder,
Mounting includes rubber vibration isolators, Stainless steel braided leader hose,
Large Cooling Fins on Cylinder, Air Filter with spares, Gearless Direct Drive Motor

GRV32533



Compressor Kit 16190, 26A Switch, 30A Fuse, Bush

33% Duty Cycle. (13 mins on, 30 mins off at 7 bar),
Max Current 23 Amps,
Max Working Pressure 10.3 Bars,
Weight 3.5 Kg.

Pumps **55** Litres per minute at 0 bar, 45.1 at 1 bar, 39 at 2 bar, 24.2 at 7 bar, 18.3 at 10 bar.

Fills 11.4L Tank 0-7bar=158 secs,
31x10.5" tyre 0-2bar=298 secs,
1-2bar=165 secs,

Also has : Automatic reset Thermal overload protector, Hi Performance PTFE piston Rings, Stainless Steel valves, Remote mountable intake filter assembly, Inline non-return valve

GRV30033



Compressor Portable 300P, 7.6m hose, 5 in one chuck, 8.3 bar guage

Runs 40mins (12 tyres) continuous up to 2 bar,
33% Duty Cycle = (15 mins on, 30 mins off at 7 bar)
Max Current 27 Amps,
Max Working Pressure 10.3 Bars,
Weight 3.9 Kg.

Pumps **67.5** Litres per minute at 0 bar, 52 at 1 bar, 45.5 at 2 bar, 23.5 at 7 bar, 14 at 10 bar.

31x10.5" tyre 0-2bar=205 secs,
1-2bar=120 secs,

Also has : Automatic reset Thermal overload protector, Hi Performance PTFE piston Rings, Stainless Steel valves, Inline fuse holder, Battery Clamps, Dual compartment carry bag

GRV44043



Compressor Portable 440P 7.6m hose, 5 in one chuck, 8.3 bar guage

Runs 30mins (9 tyres) continuous up to 2 bar,
33% Duty Cycle. (15 mins on, 30 mins off at 7 bar),
Max Current 38 Amps,
Max Working Pressure 10.3 Bars,
Weight 6.2 Kg.

Pumps **85** Litres per minute at 0 bar, 74 at 1 bar, 66 at 2 bar, 42.5 at 7 bar, 28.5 at 10 bar.

Fills 11.4L Tank 0-7bar=158 secs,
35x12.5" tyre 0-2bar=255 secs,
1-2bar=135 secs,

Also has : Also has : Automatic reset Thermal overload protector, Hi Performance PTFE piston Rings, Stainless Steel valves, Inline fuse holder, Battery Clamps, Dual compartment carry bag

GRKV00025



Hosepack 7.6m Coil, 5 In 1 Deflator/Inflator, 7Bar Gauge, Bag, Tape, 1/4FF barrel

Tyre Inflation Hose with heavy duty zippered storage bag, 7.6 Metre length (89mm coil) 6.35mm Yellow nylon pipe 13.8bar max, Gauge 0-7Bar, Open ended Chuck, Female quick-coupler. Plugs into included quick-coupler 1/4" thread male, 0.67 Kg. Continuous or intermittent deflation using a 3 position collar, 3 x inflation adapters, not for tank usage.