

# ROLLING LOBE STYLE

| GOODYEAR PART NO.  | Side View With Extended and Compressed Height           | Upper Mounting View                                  | Lower Mounting View  | Replaces These Springs   |
|--|---|--|----------------------|--|
| <b>1R11-166</b><br><br><b>Flexmember</b><br>566-24-3-048<br><br><b>Piston</b><br>566-20-7-235<br>Composite | <p>19.2<br/>7.4</p>                                     | <b>ASA-92-8-164</b><br><p>5.50<br/>9.00</p>          | <p>9.80</p>          | <b>Firestone</b><br>9295<br><b>Neway</b><br>90557121<br>Triangle<br>8417                   |
| <b>1R11-170</b><br><br><b>Flexmember</b><br>566-22-3-143<br><br><b>Piston</b><br>566-20-7-240<br>Composite | <p>6.53<br/>5.00<br/>3.84<br/>2.88<br/>20.1<br/>6.4</p> | <b>ASA-92-8-165</b><br><p>5.70<br/>9.00</p>          | <p>9.27</p>          |  |
| <b>1R11-171</b><br><br><b>Flexmember</b><br>566-22-3-057<br><br><b>Piston</b><br>566-20-7-150<br>Steel     | <p>12.0<br/>3.9</p>                                     | <b>ASA-92-8-164</b><br><p>5.50<br/>9.00</p>          | <p>8.25</p>          | <b>Firestone</b><br>9421<br><b>American Carrier</b><br>8003-003<br><b>Triangle</b><br>8468 |
| <b>1R11-191</b><br><br><b>Flexmember</b><br>566-22-3-143<br><br><b>Piston</b><br>566-20-7-239<br>Composite | <p>16.5<br/>6.0</p>                                     | <b>ASA-92-8-005</b><br><p>6.20<br/>9.00</p>          | <p>9.80</p>          | <b>Firestone</b><br>8919<br><b>Ridewell</b><br>1003588919C<br><b>Triangle</b><br>8517      |
| <b>1R11-200</b><br><br><b>Flexmember</b><br>566-22-3-021<br><br><b>Piston</b><br>566-20-7-252<br>Composite | <p>13.6<br/>5.0</p>                                     | <b>ASA-92-8-003</b><br><p>2.88<br/>6.20<br/>9.00</p> | <p>4.12<br/>9.30</p> | <b>Firestone</b><br>9376<br><b>Monaco Coach</b><br>14002<br><b>Triangle</b><br>8477        |

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- ⊙ - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/2 NPTF
- ⊗ - Combination Stud Air Fitting
- 3/8-16, on Pistons - 1/2-13
- 3/8 NPTF
- Stud - 3/4-16; Air Fitting - 1/4 NPTF