

ROLLING LOBE STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
1R11-219 Flexmember 566-22-3-021 Piston 566-20-7-287		ASA-92-8-374 SAE 45° flare, .500 O.D. tube SAE J512, .750 -16 UNF-2A 		Firestone 9617 Kenworth K-303-18 Triangle 8514
1R11-220 Flexmember 566-22-3-021 Piston 566-20-7-286		ASA-92-8-374 SAE 45° flare, .500 O.D. tube SAE J512, .750 -16 UNF-2A 		Firestone 9618 Kenworth K-303-19 Triangle 8538
1R11-221 Flexmember 566-22-3-021 Piston 566-20-7-287		ASA-92-8-373 JIC 37° flare, 1.0 O.D. tube SAE J514, 1.312-12 UNF-2A 		Firestone 9622 Kenworth K-303-22 Triangle 8537
1R11-222 Flexmember 566-22-3-021 Piston 566-20-7-286		ASA-92-8-373 JIC 37° flare, 1.0 O.D. tube SAE J514, 1.312-12 UNF-2A 		Firestone 9625 Kenworth K-303-25 Triangle
1R11-223 Flexmember 566-22-3-143 Piston 566-20-7-156		ASA-92-8-005 		Firestone 9469

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- ⊙ - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers 3/8-16, on Pistons - 1/2-13
- ⊗ - Air Fitting - 1/2 NPTF 3/8 NPTF
- ⊙ - Combination Stud Air Fitting Stud - 3/4-16; Air Fitting - 1/4 NPTF