

# ROLLING LOBE STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
<b>1R11-219</b>  Flexmember 566-22-3-021  Piston 566-20-7-287		<b>ASA-92-8-374</b> SAE 45° flare, .500 O.D. tube SAE J512, .750-16 UNF-2A 		<b>Firestone</b> 9617 <b>Kenworth</b> K-303-18 <b>Triangle</b> 8514
<b>1R11-220</b>  Flexmember 566-22-3-021  Piston 566-20-7-286		<b>ASA-92-8-374</b> SAE 45° flare, .500 O.D. tube SAE J512, .750-16 UNF-2A 		<b>Firestone</b> 9618 <b>Kenworth</b> K-303-19 <b>Triangle</b> 8538
<b>1R11-221</b>  Flexmember 566-22-3-021  Piston 566-20-7-287		<b>ASA-92-8-373</b> JIC 37° flare, 1.0 O.D. tube SAE J514, 1.312-12 UNF-2A 		<b>Firestone</b> 9622 <b>Kenworth</b> K-303-22 <b>Triangle</b> 8537
<b>1R11-222</b>  Flexmember 566-22-3-021  Piston 566-20-7-286		<b>ASA-92-8-373</b> JIC 37° flare, 1.0 O.D. tube SAE J514, 1.312-12 UNF-2A 		<b>Firestone</b> 9625 <b>Kenworth</b> K-303-25 <b>Triangle</b>
<b>1R11-223</b>  Flexmember 566-22-3-143  Piston 566-20-7-156		<b>ASA-92-8-005</b> 		<b>Firestone</b> 9469

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- ⊙ - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers 3/8-16, on Pistons - 1/2-13
- ⊗ - Air Fitting - 1/2 NPTF 3/8 NPTF
- ⊙ - Combination Stud Air Fitting Stud - 3/4-16; Air Fitting - 1/4 NPTF