

# ROLLING LOBE STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
<b>1R12-090</b>  <b>Flexmember</b> 566-24-3-038  <b>Piston</b> 566-20-7-079 Steel		<b>AS1-92-8-052</b> 		<b>Dayton</b> 352-9213 <b>Firestone</b> 9213 <b>Load Guard</b> SC2048 <b>Navistar</b> 1660581C1 501559C1 501599C2 <b>Triangle</b> 8407
<b>1R12-092</b>  <b>Flexmember</b> 566-24-3-038  <b>Piston</b> 566-20-7-080 Composite		<b>ASA-92-8-164</b> 		<b>Dayton</b> 517559C9 352-9082 <b>Fab Tek</b> 101828 <b>Firestone</b> 9082 9228 <b>Granning</b> 2727 <b>HDA</b> PMABG9082 B <b>Hendrickson</b> B-2066 36514-7 <b>Hutchens</b> 9630-01 <b>Kelderman</b> <b>Kwikk Lock / Todco</b> CP-3281 CP-5125 CP-5152 <b>Load Guard</b> SC2035 <b>Navistar</b>  <b>Neway</b> 90557006 90557027 90557037 90557054 90557075 <b>R&amp;S Truck</b> 1090217 <b>Reyco</b> 12882-01 <b>Ridewell</b> 1003589082C <b>Silent Drive Susp., Inc.</b> 201869 <b>Taurus</b> AS506-9082 <b>Toyo</b> TRL240/393 <b>Triangle</b> 8310 <b>Watson &amp; Chalin</b> AS-0011
<b>1R12-093</b> Service Assy. for 1R12-092  <b>Flexmember</b> 566-24-3-038  <b>Piston</b> Not included		<b>ASA-92-8-164</b> 	Use existing piston	Service Assembly for 1R12-092 is the 1R12-092 without the piston.  Use only with Goodyear pistons.

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/2 NPTF
- ⊗ - Combination Stud Air Fitting
- 3/8-16, on Pistons - 1/2-13
- 3/8 NPTF
- Stud - 3/4-16; Air Fitting - 1/4 NPTF