

ROLLING LOBE STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
1R12-281 Flexmember 566-24-3-066 Piston 566-20-7-080 Composite	<p>25.2 9.0</p>	AS3-92-8-121 <p>6.20 9.00</p>	<p>7.87 10.10</p>	Dayton 352-9130 Firestone 9130 9394 Fruehauf UCE-9393-1 UCE-9393-3 UCE-9393-4 Triangle 8321
1R12-303 Flexmember 566-24-3-275 Piston 566-20-7-116 Composite	<p>17.4 8.6</p>	ASA-92-8-005 <p>6.20 9.00</p>	<p>11.1</p>	Firestone Replaces 1R12-189 9780 Freightliner 6813200017 Triangle 8382 1R12-603 is the same air spring with <u>aluminum</u> piston. 1R12-603 MUST be used on 46,000 lb. suspension.
1R12-309 Flexmember 566-24-3-067 Piston 566-20-7-164 Aluminum	<p>15.5 6.0</p>	ASC-92-8-002 <p>2.88 6.20 9.00</p>	<p>5.66 9.50</p>	Dayton 352-9053 E-Z Ride 8030192 Fab Tek 10828 Firestone 9053 Fruehauf UCE-1304-2 Ridewell 1003589053C Taurus AS502-9053 Triangle 8327 Watson & Chalin AS-0095
1R12-319 Flexmember 566-24-3-097 Piston 566-20-7-079 Steel	<p>22.8 8.1</p>	ASA-92-8-218 1.25-21UNF-2A 1/2-14NPTF INSIDE <p>5.75 9.00</p>	<p>4.12 10.12</p>	
1R12-324 Flexmember 566-24-3-067 Piston 566-20-7-055 Aluminum	<p>13.5 3.7</p>	ASA-92-8-138 <p>5.50 9.00</p>	M12 X 1.75-6g <p>8.60</p>	Firestone 9565 Navistar 2027912C1 Triangle 8456

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/2 NPTF
- ⊗ - Combination Stud Air Fitting
- 3/8-16, on Pistons - 1/2-13
- 3/8 NPTF
- Stud - 3/4-16; Air Fitting - 1/4 NPTF