
















BELLOWS STYLE

| GOODYEAR PART NO. | Side View With Extended and Compressed Height | Upper Mounting View | Lower Mounting View | Replaces These Springs |
|---|---|--|---|--|
| 2B14-367 Flexmember 578-92-3-353 |  | ASA-92-8-049  | ASA-92-6-043  | Dayton 354-7123 Firestone 7123 7133 KwikLok/Todco (Jifflox) 53671 Load Guard SC2080 Navistar 1685184C1 Triangle 4345 |
| 2B14-383 Flexmember 578-92-3-356 |  | ASA-92-8-174  | ASA-92-6-118  | Firestone 7557 Reyco 19983-01 Triangle 4530 Watson & Chalin AS-0089 |
| 2B14-462 Flexmember 578-92-3-356 |  | ASA-92-8-030  | ASA-92-6-013  | Firestone 6805 Ridewell 1003586805C |
| 2B14-469 Flexmember 556-23-8-329 |  | ASA-92-8-352  | ASA-92-6-016  | Neway 90557257 |
| 2B14-470 Flexmember 578-92-3-356 |  | ASA-92-8-031  | ASA-92-6-015  | Firestone 7782 Triangle 4544 |

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- ⊙ - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/2 NPTF
- ⊗ - Combination Stud Air Fitting
- 3/8-16, on Pistons - 1/2-13
- 3/8 NPTF
- Stud - 3/4-16; Air Fitting - 1/4 NPTF