
















BELLOWS STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
3B12-304 Flexmember 578-93-3-100		ASA-92-8-002 	ASA-92-6-000 	Firestone 8006 Load Guard SC2132 Superior Suspensions, Inc. 200620 Triangle 4430 4503
3B12-310 Flexmember 578-93-3-100		ASA-92-8-005 	ASA-92-6-002 	Firestone 8027 HISTEER Silent Drive Suspensions, Inc. 200117 Triangle 4466
3B12-312 Flexmember 578-93-3-100		ASA-92-8-005 	AS1-92-6-035 	Firestone 8033 Hendrickson B-14487 Triangle 4508 4525
3B12-315 Flexmember 578-93-3-100		ASA-92-8-017 	ASA-92-6-002 	Firestone 8032 Watson & Chalin AS-0048
3B12-319 Flexmember 578-93-3-100		ASA-92-8-017 	ASA-92-6-002 	Firestone 8032 Triangle 4413

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/4 NPTF
- ⊗ - Air Fitting - 1/2 NPTF
- ⊗ - Air Fitting - 3/8 NPTF
- - Stud - 3/4-10
- ⊗ - Combination Stud Air Fitting
- ⊗ - Stud - 3/4-16; Air Fitting - 1/4 NPTF