
















BELLOWS STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
3B12-328 Flexmember 578-93-3-100		ASA-92-8-017 	ASA-92-6-111 	Firestone 7994 Triangle 4546 Watson & Chalin AS-0019-1F
3B12-329 Flexmember 578-93-3-100		ASA-92-8-159 	ASA-92-6-111 	Firestone 7995 Triangle 4547 Watson & Chalin AS-0048-1F
3B12-335 Flexmember 578-93-3-100		ASA-92-8-005 	ASA-92-6-111 	Firestone 7996 Granning 8221 Triangle 4520
3B14-351 Flexmember 578-93-3-350		ASA-92-8-028 	ASA-92-6-013 	
3B14-352 Flexmember 578-93-3-350 Replaced by 3B14-361		ASA-92-8-030 	ASA-92-6-013 	OBSOLETE Replaced by 3B14-361

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊕ - Tapped Hole on Top Retainers 3/8-16, on Pistons - 1/2-13
- ⊗ - Air Fitting - 1/4 NPTF
- ⊗ - Air Fitting - 1/2 NPTF 3/8 NPTF
- - Stud - 3/4-10
- ⊗ - Combination Stud Air Fitting Stud - 3/4-16; Air Fitting - 1/4 NPTF