













# BELLOWS STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
<b>3B14-364</b>  Flexmember 578-93-3-350		<b>ASA-92-8-100</b> 	<b>ASA-92-6-015</b> 	<b>Firestone</b> 7843 <b>Hendrickson</b> B-7100 <b>Triangle</b> 4455
<b>3B14-367</b>  Flexmember 578-93-3-350		<b>ASA-92-8-100</b> 	<b>ASA-92-6-050</b> 	<b>Dayton</b> 354-7847 <b>Firestone</b> 7847 <b>Hendrickson</b> B-8874 <b>Triangle</b> 4457
<b>3B14-451</b>  Flexmember 556-33-8-335		<b>ASA-92-8-100</b> 	<b>ASA-92-6-015</b> 	<b>Firestone</b> 7846 <b>Hendrickson</b> S-7853 <b>Triangle</b> 4456
<b>3B14-452</b>  Flexmember 556-33-8-335		<b>ASA-92-8-174</b> 	<b>ASA-92-6-056</b> 	<b>Firestone</b> 7850 <b>Triangle</b> 4441

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- ⊙ - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/2 NPTF
- ⊗ - Combination Stud Air Fitting
- 3/8-16, on Pistons - 1/2-13
- 3/8 NPTF
- Stud - 3/4-16; Air Fitting - 1/4 NPTF